

VT955/VT956 LED BEACON LUMINAIRE

VT Series is a robust, heavy-duty luminaire for general purpose and security lighting applications. The fittings are traditionally styled, but feature latest generation integrated LED light source. They are available in either wall-mount or ceiling-mount options.

ELECTRICAL PARAMETERS

Input Voltage:	120-277VAC
Power Consumption:	19.7W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industrialight Power-LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK08
IP Protection Rating:	IP65
Nominal Dimensions:	312x157mm
Construction Material:	Die-Cast Alloy & Glass
Standard Colour/Finish:	Grey
Recommended Ambient Temp:	-10 ~ +50°C

**CONFIGURATION OPTIONS**

- Available in ceiling-mount or wall-mount options
- Luminaire colour can be refinished

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	60lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	180°

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	VT955/VT956
Specify LED CCT:	3000K/4000K/4700K/6000K
Specify Beam Angle:	180°
Mounting Options:	Wall-Mount or Ceiling Mount
Input Voltage Option:	120-277VAC
Control Option:	Non-Dimmable / DALI / Phase Dim



All product details are subject to change without notice. Final specifications may vary.



toll-free: 1300 295 367



email: mail@industrialight.com.au

sales reps:



mobile: 0488 839 917



mobile: 0488 844 503