



**"It's faster than
Xircom. And it has
more drivers."**



Combo PCMCIA EthernetCard
(EC2T)
(EC2TC-D2)
(EC2TC-D3)

Benefits

- Supports Both 10BaseT & Thin Coax Ports
- Blazing 10Mbps Network Data Transfer
- No Jumpers or Switches to Set-100% Software Configurable
- Minimal Power Requirement Keeps Your Notebook PCs Powered
- Supports Virtually All Major Network Operating Systems
- Free 24-Hour Technical Support, 7 Days a Week for North America Only
- 1-Year Limited Warranty

Instant Ethernet Combo PCMCIA EthernetCard

*An Instant Network Gateway for your
PCMCIA-Equipped Notebook PCs*

Ranked #3 by PC Computing, the Combo PCMCIA EthernetCard comes with all you need to get up and running with your network software fast. Supporting all major PCMCIA driver libraries--CardSoft, Cardware, Phoenix, and more — the EthernetCard is often recognized, initialized, and ready to go the moment you pop it into your PC's PCMCIA slot. It's fully software configurable, which means that there are no jumpers or switches to set. And it's Novell NE2000-compatible, so you don't have to worry about finding the right network drivers—it's guaranteed to run with your network software.

Reliable and powerful, the Combo PCMCIA EthernetCard only runs on minimal power requirements so your notebook PC's battery power is conserved. A stainless steel casing ensures that the EthernetCard will keep you connected for years to come. Its 10Mbps data transfer rate and built-in 16KB ring buffer makes your files transfers and downloads really fly. Major industry publications agree--when it comes to performance and value, few PCMCIA network cards can match the EthernetCard's price/performance ratio.

Features

- Sturdy, Locking Media Coupler with Both 10BaseT and Thin Coax Ports on Board
- Fully IEEE 802.3 Standard-Compliant
- Novell NE2000-Compatible for Super Fast Installation
- Blazing 10 Megabits Per Second Data Transfer Rate
- 16KB Ring Buffer to Enhance Data Transfer Rate
- Automatically Senses Media Type and Polarity
- 100% Software Configurable-
No Jumpers or Switches to Set
- Extensive use of VLSI & SMT for Reliability
- Diagnostic LED Indicators for Network Status Updates
- Fully Supported by All Major PCMCIA Services
- Runs with Virtually All Major Network Software, including Windows 95, 98, NT, NetWare and Much More!
- Free Software Upgrades
- Free 24-Hour Technical Support, 7 Days a Week for North America Only
- 1-Year Limited Warranty

Specifications

Model Number	EC2T
Standards	IEEE 802.3
Protocols	CSMA/CD
Ports	1 10Base2 Thin Coax Port, 1 10/100 Autosensing RJ-45 Port
Speed Per Port	10 Mbps
Cabling Type	Category 3 or 5 UTP, or Better
LEDs	

Package Contents

- One Combo PCMCIA EthernetCard
- One Media Coupler
- User Guide and Registration Card

(Model Number:

EC2T - as shown
EC2TC-D3 - 3 LEDs
EC2TC-D2 - 2 LEDs

Environmental

Dimensions	17.3" x 7.3" x 1.7"
Unit Weight	
Power Input	5V DC
Power Consumption	
Certifications	FCC Class B, CE Mark Commercial, UL and CSA Listed
Operating Temp.	32°F to 104°F (0°C to 40°C)
Storage Temp.	-4°F to 158°F (-20°C to 70°C)
Operating Humidity	10% to 85%, Non-Condensing
Storage Humidity	5% to 90%, Non-Condensing

Linksys

17401 Armstrong Ave.
Irvine, CA 92614 USA

Information	(800) 546-5797
Technical Support	(800) 326-7114 (949) 261-1288 (949) 261-8868
Fax	
World Wide Web	http://www.linksys.com
Email	sales@linksys.com support@linksys.com

China

Tech Support	(10) 6432 1920
Sales	(10) 6432 1923
Fax	(10) 6437 6891

Germany

Telephone	(0) 8166 684279
Fax	(0) 8166 68274

Japan

Telephone	(03) 5259-5139
Fax	(03) 5259-5117

Singapore

Telephone	552-8998
Fax	552-1024

Thailand

Telephone	717-0770
Fax	717-0738

United Kingdom

Tech Support	0870 7393939
Sales	01245 352403
Fax	0870 7393938

